



PROTECTIVE INDUSTRIAL PRODUCTS



FALL PROTECTION CATALOG

www.pipcanada.ca



DYNAMIC, THE REFERENCED LEADER FOR PPE IN CANADA, IS NOW A PROUD PART OF THE PIP GLOBAL FAMILY

Protective Industrial Products, Inc. (PIP) was initially established in 1984 as a supplier of work gloves. Today we are a global provider of a vast array of consumable personal protective equipment to multiple industries and channels of distribution.

Our Dynamic branded safety equipment are proudly made to meet all the safety regulations and/or standards required in Canada, the United States, Europe and Latin America. These products must be certified by multiple certification bodies such as CSA, ANSI, CE, NIOSH and when permitted, we are proud to display these logos on our products. This ensures that you can place your trust in products that meet the highest possible standards of quality.




PRODUCTS & PROGRAMS THAT SUPPORT YOUR BUSINESS OBJECTIVES

Our manufacturing facilities in Canada are committed to bringing to market products that provide the best possible comfort, fit, and value. But bringing you the best doesn't stop there. Our dedicated team of product managers and specialists have over 100 years of collective experience, ensuring that you receive expert support and enabling you to conduct trainings and risk assessment in the workplace, in addition to helping your safety committee select the proper PPE. Furthermore, we are continuously developing our website that is second to none, thanks to powerful yet intuitive tools such as our product selector and 3SP™ assessment.



At PIP Canada we strive to design and produce the best PPE in the market, and make sure that all employees arrive home safe and sound everyday.



**BRINGING THE
BEST OF THE WORLD
TO YOU®**

ABCDs OF FALL PROTECTION

To succeed in this unforgiving category, you need to be cognizant of your ABCDs. PIP Canada is committed to developing fall protection PPE that delivers exceptional performance for the harshest conditions, and in the widest array of applications.

A **ANCHORAGE** connectors that provide a secure connection to structures, thus allowing an attachment point.

Cable Slings	39
Pass Through Slings	39
D-Ring Anchors	40
Removable Concrete Anchors	40
Toggle Anchors	40
Swivel Anchors	40
Beam Anchors	40
Door/Window Anchors	41
Roof Brackets & 4 Persons	41
Temporary Rope Horizontal Lifeline	41

B **BODY** wear worn by the user, which includes harnesses as well as other personal protective equipment.

Dyna-Pro™ Aluminum Harnesses	6
Dyna-Pro™ Universal Harnesses	7
Dyna-I™ Universal Harnesses	8
Hybrid Econo Harnesses	9
B-Compliant Harnesses	10
Dyna-Lite™ Harnesses	11
Dyna-Tower™ Aluminum Harnesses	12
Y-Trend™ Aluminum Harnesses	14
V-Trend™ Aluminum Harnesses	14
Easy Don X-Trend™ Aluminum Harnesses	15
Easy Don X-Trend™ Harnesses	16
X-Trend™ Harnesses	17
Miss Dyna™ X-Trend™ Aluminum Harnesses	18
TPU Coated Harnesses	19
Arborist Aluminum Harnesses	19
Kevlar® FR Harnesses for Welders	20
Kevlar® FR Harnesses for Electricians	21
Anti Corrosion Harnesses	22
Dyna-Viz™ Harnesses	22
Construction Pro™ Aluminum Harnesses	23
Construction Eco™ Harnesses	23
Combination Harnesses	24
Industrial Body Belts & Miner's Belt	25

C **CONNECTING** devices that link the body wear to the anchorage connectors, critical to the system as it usually incorporates energy absorbing technology.

Personal Self-Retracting Lifelines (SRL)	26
Self-Retracting Lifelines (SRL)	27
Rope & Web Lanyards	28
Lanyards	29-34
Energy Absorbers & Extended D-Ring	35
Work Positioning Products	35
Hooks & Carabiners	36
Vertical Rope Lifelines	37
Rope Grabs	38
Compliance Kits & Roofer's Kits	43
Tool Tethering	44-45
Inspection Tags, Storage Bags	46

D **DESCENT** and rescue products that form a key component of any rescue plan in order to ensure a timely response.


Rescue & Retrieval Systems	41
Tripods & Accessories	42




Harness Sizing & Class

HARNESS APPLICATION CLASS

Harnesses are available for a variety of applications signified by the pictograms and definitions below.



HARNESS SIZING CHART



BELT SIZING CHARTS

Belt Size	Waist Measurement	
	Centimeters	Inches
SMALL	71 to 91 cm	28 IN to 36 IN
MEDIUM	81 to 101 cm	32 IN to 40 IN
LARGE	91 to 111 cm	36 IN to 44 IN
XLARGE	101 to 122 cm	40 IN to 48 IN
XXLARGE	111 to 132 cm	44 IN to 52 IN
XXXLARGE*	122 to 142 cm	48 IN to 56 IN

* This size is available upon request

CONNECTION DEVICES



PERSONALIZATION

OUR HARNESSES AND LANYARDS PROVIDE A COST-EFFECTIVE OPPORTUNITY TO PROMOTE BOTH YOUR BRAND IMAGE AND YOUR HEALTH & SAFETY MESSAGE


Identification on the jobsite is now more important than ever. We have a team dedicated to providing you with the best personalization services, allowing you to benefit from:

- ▶ Increased visibility on the jobsite
- ▶ Improved employee morale
- ▶ Improved company image
- ▶ Reduced theft of PPE



CUSTOM WEBBING COLORS AVAILABLE

SERVICES INCLUDE



Harness Personalization


Ability to print a custom color logo or message onto the harness backstrap. Furthermore, the ability to select any two color combinations for the top and bottom of the harness. Colors selected must be from a pre-determined list already certified with CSA.

Lanyard Personalization

Ability to print a custom color logo or message onto the lanyards that have a 4.5 cm (1.75") webbing width.



Dyna-Pro™ Aluminum



FPX1004D
Front



FPX1004D
Back



FPX1001DG
Front



FPX1001DG
Back



FPX1001EDG
Front



FPX1001EDG
Back

PROFESSIONAL VEST STYLE HARNESS WITH ALL ALUMINUM HARDWARE. INTEGRATED PAD ON SHOULDERS & LEG STRAPS. 5 POINT ADJUSTMENT.

Designed for comfort by eliminating all unnecessary weight and bulkiness. The hardware is made of lightweight aluminum, for a weight savings of 25% and exceptional corrosion resistance. The Dynamic® back pad focuses on comfort by relieving pressure points at your shoulders and the back of the legs. The non-bulky pad also eliminates heat zones, weight and reduces the overall mass of the harness, making this one of the most comfortable harnesses you will wear. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPX1001D	A	B	ALUMINUM BAYONET
FPX1001ED	A	B / X	ALUMINUM BAYONET
FPX1001DG	A	B	TONGUE BUCKLES
FPX1001EDG	A	B / X	TONGUE BUCKLES

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPX1003D	A / P	B / S	ALUMINUM BAYONET
FPX1003DG	A / P	B / S	TONGUE BUCKLES

Work Positioning / Confined Spaces & Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPX1002D	A / L	F / B	ALUMINUM BAYONET
FPX1004D	A / P / L	F / B / S	ALUMINUM BAYONET
FPX1004DG	A / P / L	F / B / S	TONGUE BUCKLES
FPX1004SD	A / E / L	F / B / E	ALUMINUM BAYONET
FPX1004SDG	A / E / L	F / B / E	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Dyna-Pro™ Universal



FP1001EDG
Front



FP1001EDG
Back



FP1004SD
Front



FP1004SD
Back

PROFESSIONAL VEST STYLE HARNESS WITH INTEGRATED CUSHION ON BACK, SHOULDERS & LEG STRAPS AND 5 POINT ADJUSTMENT.

Designed with ease of donning top of mind, this harness also features lightweight breathable padding only where required. The lack of excessive padding results in the elimination of unnecessary hot zones and an increase in the mobility of the wearer, for comfort that lasts all day long. The lightest harness in its category. It also has trauma straps to provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP1001D	A	B	BAYONET
FP1001ED	A	B / X	BAYONET
FP1001DG	A	B	TONGUE BUCKLES
FP1001EDG	A	B / X	TONGUE BUCKLES

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP1003D	A / P	B / S	BAYONET
FP1003DG	A / P	B / S	TONGUE BUCKLES

Work Positioning / Confined Spaces & Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP1002D	A / L	F / B	ALUMINUM BAYONET
FP1004D	A / P / L	F / B / S	ALUMINUM BAYONET
FP1004DG	A / P / L	F / B / S	TONGUE BUCKLES
FP1004SD	A / E / L	F / B / E	ALUMINUM BAYONET
FP1004SDG	A / E / L	F / B / E	TONGUE BUCKLES



Class A



Class P



Class E



Class L




Class D

CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Dyna-I™ Universal



FP2001BD
Front



FP2001BD
Back



FP2004BDG
Front



FP2004BDG
Back

VEST STYLE HARNESS WITH 5 POINT ADJUSTMENT.

Designed for comfort and ease of use, including fully adjustable shoulder and chest straps that can be optimally positioned to meet your specific needs. The polyester webbing protects against UV rays and provides excellent resistance to most chemicals. Multiple combinations of connectors and D-rings are available for any application. All Dynamic® harnesses offer a sub-pelvic strap with a sewn pattern for maximum comfort. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2001D	A	B	FRICITION
FP2001ED	A	B / X	FRICITION
FP2001BD*	A	B	BAYONET
FP2001BED*	A	B / X	BAYONET
FP2001DG	A	B	TONGUE BUCKLES
FP2001EDG	A	B / X	TONGUE BUCKLES
FP2001BDG*	A	B	TONGUE BUCKLES
FP2001BEDG*	A	B / X	TONGUE BUCKLES

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2003D	A / P	B / S	FRICITION
FP2003ED	A / P	B / X / S	FRICITION
FP2003BD*	A / P	B / S	BAYONET
FP2003BED*	A / P	B / X / S	BAYONET
FP2003DG	A / P	B / S	TONGUE BUCKLES
FP2003EDG	A / P	B / X / S	TONGUE BUCKLES
FP2003BDG*	A / P	B / S	TONGUE BUCKLES
FP2003BEDG*	A / P	B / X / S	TONGUE BUCKLES

Work Positioning / Confined Space Harnesses


PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2002BD	A / L	F / B	BAYONET
FP2002BDG*	A / L	F / B	TONGUE BUCKLES
FP2003SD	A / E	B / E	FRICITION
FP2003SDG*	A / E	B / E	TONGUE BUCKLES
FP2003BSD*	A / E	B / E	BAYONET
FP2003BESD*	A / E	B / E	BAYONET
FP2003BSDG*	A / E	B / E	TONGUE BUCKLES
FP2004BD*	A / P / L	F / B / S	BAYONET
FP2004BDG*	A / P / L	F / B / S	TONGUE BUCKLES
FP2004SBDG*	A / E / L	F / B / S	TONGUE BUCKLES
FP2005D	A / P / E	B / S / E	FRICITION
FP2005DG	A / P / E	B / S / E	TONGUE BUCKLES
FP2005BD*	A / P / E	B / S / E	BAYONET
FP2005BDG*	A / P / E	B / S / E	TONGUE BUCKLES
FP2006BD	A / P / E / L	F / B / S / E	BAYONET

* Bayonet style connector on adjustable chest strap.



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Hybrid Econo



FP2501D
Front



FP2501D
Back



FP2503DG
Front



FP2503DG
Back

BASIC, ECONOMICAL AND FULLY ADJUSTABLE HARNESS.

A basic but reliable harness that is adjustable at the torso, it provides similar benefits to a regular mid-range harness but at an economical price. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2501D	A	B	FRICTION
FP2501DG	A	B	TONGUE BUCKLES

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2503D	A / P	B / S	FRICTION
FP2503DG	A / P	B / S	TONGUE BUCKLES

Work Positioning / Confined Spaces


PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2505D	A / P / E	B / S / E	FRICTION
FP2505DG	A / P / E	B / S / E	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



B-Compliant



FP4001DGU
Front



FP4001DGU
Back



FP4003SDU
Front



FP4003SDU
Back



FP4005DG
Front



FP4005DG
Back

BASIC, ECONOMICAL HARNESS WITH 3 POINT ADJUSTMENT.

Ideal for the occasional user, this basic yet comfortable design configuration offers reliable protection at an economical price. Manufactured from high quality polyester webbing with adjustable leg straps, it provides resistance to UV rays and most chemicals. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP4001DU	A	B	FRICTION
FP4001DGU	A	B	TONGUE BUCKLES

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP4003DU	A / P	B / S	FRICTION
FP4003DGU	A / P	B / S	TONGUE BUCKLES


Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP4003SDU	A / E	B / E	FRICTION
FP4003SDGU	A / E	B / E	TONGUE BUCKLES
FP4005DU	A / P / E	B / S / E	FRICTION
FP4005DGU	A / P / E	B / S / E	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
 Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Dyna-Lite™



FP4101DGU
Front



FP4101DGU
Back

ECONOMICAL FULL BODY HARNESS WITH 3 OR 5 POINT ADJUSTMENT.

Ideal for the occasional user, this design configuration offers reliable protection at an economical price. Features passthrough mating buckles with optional grommet hardware, two tearaway lanyard keepers, and durable protected labels. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2601DU	A	B	FRICTION
FP2601DGU	A	B	TONGUE BUCKLES
FP2603DU	A / P	B / S	FRICTION
FP2603DGU	A / P	B / S	TONGUE BUCKLES

Work Positioning / Ladder Climbing


PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP2604DU	A / P / L	B / S / F	FRICTION
FP2604DGU	A / P / L	B / S / F	TONGUE BUCKLES

Work Positioning

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP4101DU	A	B	FRICTION
FP4101DGU	A	B	TONGUE BUCKLES
FP4103DU	A / P	B / S	FRICTION
FP4103DGU	A / P	B / S	TONGUE BUCKLES



Class A



Class P



Class E



Class L




Class D

CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Dyna-Tower™ Aluminum



FPT05DDD
Front



FPT05DDD
Back



FPT07DSC
Front



FPT07DSC
Back



FPT07DWC
Front



FPT07DWC
Back

VEST STYLE HARNESS WITH INTEGRATED PADDING, PERMANENT ATTACHED BELT WITH LUMBAR SUPPORT AND OPTIONAL SADDLE OR WORKSEAT.

Designed for the tower industry where comfort, fit and weight are critical. The integrated breathable padding is optimally sized to reduce unnecessary heat zones, while the all-aluminum hardware keeps weight minimal. Optional removable saddle or workseat provides additional comfort when working at heights for longer periods of time. Two frontal D-rings provide versatility when connecting to ladder systems or rescue/rope access devices. The comfortable integrated belt is specifically designed to ensure proper load transfer from the belt to the harness to maximize the load distribution to the body. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Work Positioning / Confined Space Harnesses with Integrated Belt

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPT04DDC	A / P / L	F / B / S (2)	ALUMINUM BAYONET
FPT04DDD	A / P / L	F / B / S (2)	TONGUE BUCKLES
FPT05DDC	A / P / L	F (2) / B / S (2)	ALUMINUM BAYONET
FPT05DDD	A / P / L	F (2) / B / S (2)	TONGUE BUCKLES

With Integrated Saddle

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPT07DSC	A / P / L / D	F (2) / B / S (2) / SADDLE (2)	ALUMINUM BAYONET
FPT07DSD	A / P / L / D	F (2) / B / S (2) / SADDLE (2)	TONGUE BUCKLES

With Integrated Work Seat

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPT07DWC	A / P / L / D	F (2) / B / S (2) / WORK SEAT (2)	ALUMINUM BAYONET
FPT07DWD	A / P / L / D	F (2) / B / S (2) / WORK SEAT (2)	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

FALL PROTECTION





Y-Trend™ Aluminum

SA CERTIFIED



FPY05DFF
Front

FPY05DFF
Back

SUSPENSION HARNESS WITH INTEGRATED PADDING AND HORIZONTAL D-RING. PERMANENT ATTACHED BELT WITH LUMBAR SUPPORT.

Designed for rope access and rescue, the bottom of the harness allows the user to suspend naturally for long periods of times while remaining comfortable. The upper portion has a unique configuration which makes the harness intuitive to don and eliminating the need to step into it and pull over. The integrated breathable padding is optimally sized to reduce unnecessary heat zones, while the all-aluminum hardware makes it one of the lightest on the market. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.



FP550/1
Lumbar Support

Suspension / Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPY05DFF	A / P / L / D	F / B / S	ALUMINUM BAYONET
FPY05DFH	A / P / L / D	F / B / S	TONGUE BUCKLES

Back Support Kit

PART NO	DESCRIPTION	SIZE
FP550/1	DELUXE "ADD ON" LUMBAR SUPPORT FOR BELTS WITH CUSHION, COLOR RED AND BLACK. COMES WITH A TOOL BELT MODEL FP5000D. THIS KIT CAN BE ADDED TO ALL HARNESSSES OF FP1000, FP2000 AND FP2500 SERIES.	S/M OR L/XL



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

V-Trend™ Aluminum

SA CERTIFIED



FPW06DG
Front

FPW06DG
Back

SUSPENSION HARNESS WITH INTEGRATED PADDING AND VERTICAL D-RING. PERMANENT ATTACHED BELT WITH LUMBAR SUPPORT.

Designed for rope access and rescue, the bottom of the harness allows the user to suspend naturally for long periods of times while remaining comfortable. The upper portion has a unique configuration which makes the harness intuitive to don and eliminating the need to step into it and pull over. The integrated breathable padding is optimally sized to reduce unnecessary heat zones, while the all-aluminum hardware makes it one of the lightest on the market. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.


Suspension / Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPW06D	A / P / L / D	F / B / S	ALUMINUM BAYONET
FPW06DG	A / P / L / D	F / B / S	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Easy Don X-Trend™ Aluminum



FPV01DG
Front



FPV01DG
Back

EASY TO DON LIGHTWEIGHT HARNESS WITH INTEGRATED PADDING. 4 POINTS OF ADJUSTMENT.

Designed for comfort and ease of donning by eliminating the need to pull the harness over your head. The hardware is made of lightweight aluminum, for a weight savings of 25% and exceptional corrosion resistance. The Dynamic® back pad focuses on comfort by relieving pressure points at your shoulders and the back of the legs. The non-bulky pad also eliminates heat zones, weight and reduces the overall mass of the harness, making this one of the most comfortable harnesses you will wear. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.



FPV06D
Front

Fall Arrest / Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPV01D	A	B	ALUMINUM BAYONET
FPV01DG	A	B	TONGUE BUCKLES
FPV02D	A / L	F / B	ALUMINUM BAYONET
FPV02DG	A / L	F / B	TONGUE BUCKLES

Work Positioning / Confined Space / Ladder Climbing Harnesses


PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPV04D	A / P / L	F / B / S	ALUMINUM BAYONET
FPV04DG	A / P / L	F / B / S	TONGUE BUCKLES
FPV04SD	A / E / L	F / B / E	ALUMINUM BAYONET
FPV04SDG	A / E / L	F / B / E	TONGUE BUCKLES
FPV06D	A / P / E / L	F / B / S / E	ALUMINUM BAYONET
FPV06DG	A / P / E / L	F / B / S / E	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Easy Don X-Trend™



FPU01DG
Front



FPU01DG
Back



FPU06D
Front



FPU06D
Back



FPU06DG
Front



FPU06DG
Back

EASY TO DON HARNESS WITH INTERGRATED PADDING. 4 POINTS OF ADJUSTMENT.


Designed for comfort and ease of donning by eliminating all unnecessary bulkiness. The Dynamic® back pad focuses on comfort by relieving pressure points at your shoulders and the back of the legs. The non-bulky pad also eliminates heat zones, weight and reduces the overall mass of the harness, making this one of the most comfortable harnesses you will wear. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest / Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPU01D	A	B	BAYONET
FPU01DG	A	B	TONGUE BUCKLES
FPU02D	A / L	F / B	BAYONET
FPU02DG	A / L	F / B	TONGUE BUCKLES


Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPU04D	A / P / L	F / B / S	BAYONET
FPU04DG	A / P / L	F / B / S	TONGUE BUCKLES
FPU04SD	A / E / L	F / B / E	BAYONET
FPU04SDG	A / E / L	F / B / E	TONGUE BUCKLES
FPU06D	A / P / E / L	F / B / S / E	BAYONET
FPU06DG	A / P / E / L	F / B / S / E	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
 Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

X-Trend™



FP3002D
Front



FP3002D
Back



FP3004SD
Front



FP3004SD
Back

TRADITIONAL HARNESS WITH 4 POINTS OF ADJUSTMENT.

These harnesses are manufactured from polyester webbing, and have a sub-pelvic strap that distributes the forces in case of a fall. CSA certified. Meets and exceeds ANSI and OSHA regulations.



FP3006DG
Front



FP3006DG
Back

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP3001DG	A	B	TONGUE BUCKLES
FP3002D	A / L	F / B	FRICTION
FP3002DG	A / L	F / B	TONGUE BUCKLES

Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP3004D	A / P / L	F / B / S	FRICTION
FP3004SD	A / E / L	F / B / E	FRICTION
FP3004DG	A / P / L	F / B / S	TONGUE BUCKLES
FP3006D	A / P / E / L	F / B / S / E	FRICTION
FP3006DG	A / P / E / L	F / B / S / E	TONGUE BUCKLES



Class A



Class P



Class E



Class L




Class D

CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Miss-Dyna™ X-Trend™ Aluminum



FPVW02DG
Front



FPVW02DG
Back



FPVW04DG
Front



FPVW04DG
Back

EASY TO DON LIGHTWEIGHT HARNESS WITH INTEGRATED PADDING. 4 POINTS OF ADJUSTMENT.

Ideal for female workers where the traditional H-Style harness does not fit properly around the user's chest, this design provides a larger range of mobility. It is also optimal for ladder climbing as there is less slack with the front D-Ring vs H-Style harnesses. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest / Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPVW02D	A / L	F / B	ALUMINUM BAYONET
FPVW02DG	A / L	F / B	TONGUE BUCKLES

Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPVW04D	A / P / L	F / B / S	ALUMINUM BAYONET
FPVW04DG	A / P / L	F / B / S	TONGUE BUCKLES

Class A



Class P



Class E



Class L




Class D



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

TPU Coated



FPC2001BD
Front



FPC2001BD
Back

VEST STYLE HARNESS WITH 5 POINT ADJUSTMENTS AND TPU COATED WEBBING FOR EXTRA DURABILITY.

Ideal for dirty, contaminated or clean environments. The TPU coating provides resistance to abrasions, weld splatter, chemicals, paint, grease and dirt. Harness can be wiped clean, making it easier to inspect and reducing the frequency of replacement. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.



FPUPAD
Shoulder and Leg Pad

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPC2001BD	A	B	BAYONET
FPC2001BDG	A	B	TONGUE BUCKLES

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPC2003BD	A/P	B/S	BAYONET
FPC2003BDG	A/P	B/S	TONGUE BUCKLES


Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPC2005BD	A/P/E	B/S/E	BAYONET
FPC2005BDG	A/P/E	B/S/E	TONGUE BUCKLES

Shoulder and Leg Pad

PART NO	DESCRIPTION
FPUPAD	OPTIONAL SHOULDER / LEG PADDING WITH VELCRO® / SOLD BY PAIR

Arborist Aluminum



FPJ04D
Front



FPJ04D
Back

SUSPENSION HARNESS WITH INTEGRATED PADDING. PERMANENT ATTACHED BELT WITH LUMBAR SUPPORT.

Designed for rope access and rescue; it allows the user to suspend naturally for long periods while remaining comfortable. The upper portion has a unique configuration which makes it intuitive to don and eliminating the need to step into it and pull over. The integrated breathable padding is optimally sized to reduce heat zones, and aluminum hardware makes it lightweight. CSA certified. Meets and exceeds ANSI and OSHA regulations.



FPJRB
Replacement Bridge

Arborist Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPJ04D	A/P/L/D	F/B/S	ALUMINUM BAYONET

Replacement Bridge

PART NO	DESCRIPTION
FPJRB	REPLACEMENT BRIDGE

Class A



Class P



Class E



Class L




Class D



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Kevlar® FR for Welders



FPK2002BD
Front



FPK2002BD
Back



FPK2005BDG
Front



FPK2005BDG
Back

HARNESSES FOR WELDERS.

Manufactured from Kevlar® webbing to provide exceptional protection against cuts and abrasions, as well as high heat resistance to sparks and flames, along with the security of maximum protection in case of a fall. ASTM F887 Arc Flash and is CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPK2001BD	A	B	BAYONET

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPK2003BD	A / P	B / S	BAYONET

Work Positioning / Confined Space & Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPK2002BD	A / L	F / B	BAYONET
FPK2005BD	A / P / E	B / S / E	BAYONET
FPK2005BDG	A / P / E	B / S / E	TONGUE BUCKLES
FPK2006BD	A / P / E / L	F / B / S / E	BAYONET

Class A



Class P



Class E



Class L




Class D



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Kevlar® FR for Electricians



FPE2001D
Front



Coated Metal
D-ring



FPE2001D
Back

COATED HARNESES FOR ELECTRICIANS.

Manufactured from Kevlar® webbing to provide exceptional protection against cuts and abrasions, as well as high heat resistance to sparks and flames, along with the security of maximum protection in case of a fall. The electrician's version features coated metal components rendering the harness completely dielectric. ASTM F887 Arc Flash and is CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPE2001D	A	B	COATED FRICTION

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPE2003D	A / P	B / S	COATED FRICTION

Work Positioning / Confined Space & Ladder Climbing Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPE2003SD	A / E	B / E	COATED FRICTION
FPE2005D	A / P / E	B / S / E	COATED FRICTION

Class A



Class P



Class E



Class L




Class D



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Anti-Corrosion



FPD2503D
Front



FPD2503D
Back

BASIC, ECONOMICAL AND FULLY ADJUSTABLE HARNESSES WITH PVC COATED HARDWARE.

Designed with PVC coated hardware for protection in highly corrosive environments. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses


PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPD2501D	A	B	FRICTION

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPD2503D	A / P	B / S	FRICTION
FPD2503SD	A / E	B / E	FRICTION

Work Positioning / Confined Space Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPD2505D	A / P / E	B / S / E	FRICTION



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Dyna-Viz™

MADE FROM CSA CERTIFIED COMPONENTS



FP25R5D
Front




FP25R5D
Back

HARNESS WITH REFLECTIVE WEBBING AND 5 POINT ADJUSTMENT.

Designed with orange webbing and reflective striping to provide high visibility in low light environments. Trauma straps provide crucial additional time in a rescue situation.


Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FP25R1D	A	B	FRICTION
FP25R3D	A / P	B / S	FRICTION
FP25R5D	A / P / E	B / S / E	FRICTION



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Construction Pro™



FPMX1G1D0DR
Front

FPMX1G1D0DR
Back

HI-VISIBILITY VEST STYLE HARNESS WITH 5 POINT ADJUSTMENT AND INTEGRATED BREAKAWAY TOOL BELT.

Manufactured of reinforced material designed to support the additional weight of heavy-duty tools. A 0.5" wide reflective stripe provides high visibility in low light conditions, and the tool belt breaks away in the event of a fall, eliminating the risk of injury to the abdomen. The hardware is made of lightweight aluminum, for a weight savings of 25% and exceptional corrosion resistance. The integrated shoulder pad and leather lumbar support are optimally sized to reduce heat zones while increasing comfort. Trauma straps provide crucial additional time in a rescue situation. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPMX101D0DR	A	B	ALUMINUM BAYONET
FPMX1G1D0DR	A	B	TONGUE BUCKLES


Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPMX101D2DR	A / P	B / S (ON BELT)	ALUMINUM BAYONET
FPMX103D0DR	A / P	B / S	ALUMINUM BAYONET
FPMX1G1D2DR	A / P	B / S (ON BELT)	TONGUE BUCKLES
FPMX1G3D0DR	A / P	B / S	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Construction Eco™



FPM503D0DC
Front

FPM503D0DC
Back

VEST STYLE HARNESS WITH 5 POINT ADJUSTMENT.

Equipped with a floating reinforced tool belt to support the weight of heavy-duty tools. The removable shoulder padding is optimized to reduce heat zones and minimize bulk. Grommet options make it easier to adjust and readjust as necessary for different weather conditions. CSA certified.

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPM501D0DC	A	B	FRICTION
FPM5G1D0DC	A	B	TONGUE BUCKLES

Work Positioning Harnesses


PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPM503D0DC	A / P	B / S (ON BELT)	FRICTION
FPM5G3D0DC	A / P	B / S	TONGUE BUCKLES



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)



Combination Harnesses



FPM101D
Front



FPM101D
Back



FPM251D
Front



FPM251D
Back

WITH BELT AND LUMBAR SUPPORT.

Lower back lumbar padding provides the user with increased comfort and support. Versatile belt can be used as a tool belt while ensuring the weight is properly distributed across the body. Other harness & belt combinations can be made upon request.



FPM1G1D
Front



FPM1G1D
Back

Fall Arrest Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPM101D	A	B	BAYONET
FPM201D	A	B	BAYONET
FPM251D	A	B	FRICTION

Work Positioning Harnesses

PART NO	CLASS	D-RING	LEG STRAP CONNECTORS
FPM103D	A / P	B / S	BAYONET
FPM203D	A / P	B / S	BAYONET
FPM253D	A / P	B / S	FRICTION
FPM1G1D	A	B	TONGUE BUCKLES
FPM2G1D	A	B	TONGUE BUCKLES
FPM5G1D	A	B	TONGUE BUCKLES
FPM1G3D	A / P	B / S	TONGUE BUCKLES
FPM2G3D	A / P	B / S	TONGUE BUCKLES
FPM5G3D	A / P	B / S	TONGUE BUCKLES

Class A



Class P



Class E



Class L




Class D



CLASS (Legend): A Fall Arrest | P Work Positioning | E Confined Spaces | L Ladder Climbing | D Suspension & Descent
Metallic D-ring: F Front | B Back (adjustable) | S Sides or Hips | E Shoulders | L Chest Strap Buckle | X Extension (D-ring)

Industrial Body Belts



FP5000D



FP5001D



FP5002D


Made of 1.75" (4.5 cm) polyester webbing, they are light and comfortable. Ideal for travel restraint and for certain work positioning. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Industrial Body Belts

PART NO	DESCRIPTION	D-RING (S)
FP5000D	TOOL BELT	0
FP5001D	TRAVEL RESTRAINT BELT	1
FP5002D	WORK POSITIONING BELT	2

Important: Do not use if there is a potential danger for falls. Available in 4 sizes: Small, Medium, Large and X-Large (X-Small and XX-Large available on request). See sizing references on page 3 of this catalogue.

Miner's Belt



FP51001D



FP52001D



FP500



FP550

Designed to be tough, comfortable and user friendly. They are made of 2" (5.0 cm) reinforced polyester webbing that is highly resistant to UV rays and most chemicals. Straps are made of durable belting material highly resistant to abrasion and humidity. CSA certified. Meets and exceeds ANSI and OSHA regulations.

Miner's Belts

PART NO	DESCRIPTION	D-RING (S)
FP51001D*	MADE OF TIGHT WEAVE POLYESTER 2" (5.0 CM) WEBBING WITH (1) BATTERY STRAP REINFORCED AND REMOVABLE	1
FP52001D*	MADE OF TIGHT WEAVE POLYESTER 2" (5.0 CM) WEBBING WITH (1) BATTERY STRAP REINFORCED AND REMOVABLE PLUS (1) FIXED RESCUE STRAP	1
FP52000D*	MADE OF TIGHT WEAVE POLYESTER 2" (5.0 CM) WEBBING WITH (1) BATTERY STRAP REINFORCED AND REMOVABLE PLUS (1) FIXED RESCUE STRAP	0

Lumbar Support for Industrial & Miner's Belts

PART NO	DESCRIPTION
FP500	LUMBAR SUPPORT FOR BELT - BLACK COLOR
FP550	DELUXE LUMBAR SUPPORT WITH PADDING. COLOR: RED INSIDE AND BLACK OUTSIDE

Important: Do not use if there is a potential danger for falls. *Available in sizes from 28" to 56".



Personal Self-Retracting Lifelines (SRL)



FP1102W



FP1101W
Front

Side



FP1102DW



FP1101DWB



FP2203W



FP2206W

Manufactured with 1" UHMWPE/Polyester webbing and the device housing can be connected to a harness or to an anchor. Available in both single and double leg units. CSA certified as Class SRL. Fall indicator built into the webbing of the lifeline. Meets and exceeds ANSI and OSHA regulations. RATED FOR 310 LB WEIGHT CAPACITY.

Single Leg Self-Retracting Lifelines Class SRL

PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP1101W	UHMWPE/Polyester	TRIPLE ACTION CARABINER	SMALL HOOK	6 FT (1.82 M)
FP1101WA	UHMWPE/Polyester	TRIPLE ACTION CARABINER	MEDIUM HOOK	6 FT (1.82 M)
FP1101WB	UHMWPE/Polyester	TRIPLE ACTION CARABINER	LARGE HOOK	6 FT (1.82 M)
FP1101WC	UHMWPE/Polyester	TRIPLE ACTION CARABINER	ALUM. LARGE HOOK	6 FT (1.82 M)
FP1101DWD	UHMWPE/Polyester	TRIPLE ACTION CARABINER	TRIPLE ACTION CARABINER	6 FT (1.82 M)
FP1102W	UHMWPE/Polyester	TRIPLE ACTION CARABINER	SMALL HOOK	7 FT (2.15 M)
FP1102WA	UHMWPE/Polyester	TRIPLE ACTION CARABINER	MEDIUM HOOK	7 FT (2.15 M)
FP1102WB	UHMWPE/Polyester	TRIPLE ACTION CARABINER	LARGE HOOK	7 FT (2.15 M)
FP1102WC	UHMWPE/Polyester	TRIPLE ACTION CARABINER	ALUM. LARGE HOOK	7 FT (2.15 M)

Double Leg Self-Retracting Lifelines Class SRL

PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP1101DW	UHMWPE/Polyester	TRIPLE ACTION CARABINER	SMALL SNAP HOOK (2)	6 FT (1.82 M)
FP1101DWA	UHMWPE/Polyester	TRIPLE ACTION CARABINER	MEDIUM SNAP HOOK (2)	6 FT (1.82 M)
FP1101DWB	UHMWPE/Polyester	TRIPLE ACTION CARABINER	LARGE SNAP HOOK (2)	6 FT (1.82 M)
FP1101DWC	UHMWPE/Polyester	TRIPLE ACTION CARABINER	LARGE ALUM. SNAP HOOK (2)	6 FT (1.82 M)
FP1101DWD	UHMWPE/Polyester	TRIPLE ACTION CARABINER	TRIPLE ACTION CARABINER	6 FT (1.82 M)
FP1102DW	UHMWPE/Polyester	TRIPLE ACTION CARABINER	SMALL HOOK (2)	7 FT (2.15 M)
FP1102DWA	UHMWPE/Polyester	TRIPLE ACTION CARABINER	MEDIUM HOOK (2)	7 FT (2.15 M)
FP1102DWB	UHMWPE/Polyester	TRIPLE ACTION CARABINER	LARGE HOOK (2)	7 FT (2.15 M)
FP1102DWC	UHMWPE/Polyester	TRIPLE ACTION CARABINER	ALUM. LARGE HOOK (2)	7 FT (2.15 M)


Single Leg Self-Retracting Lifelines Class SRL

PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP2203W	UHMWPE/Polyester	SMALL HOOK	TRIPLE ACTION CARABINER	11 FT (3.4 M)
FP2203WA	UHMWPE/Polyester	SMALL HOOK	MEDIUM HOOK	11 FT (3.4 M)
FP2203WB	UHMWPE/Polyester	SMALL HOOK	LARGE HOOK	11 FT (3.4 M)
FP2203WC	UHMWPE/Polyester	SMALL HOOK	ALUM LARGE HOOK	11 FT (3.4 M)
F2206W	UHMWPE/Polyester	SMALL HOOK	TRIPLE ACTION CARABINER	20 FT (6.1 M)

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Large: FP5395ALL | **Triple Action Carabiner:** FP244

Self-Retracting Lifelines (SRL)



FP2YY11C / FP2YY15C /
FP2AA06C



FP2AA10C / FP2AA15C



FP2YY65C

Manufactured with composite housing to make the units lightweight while ensuring strength properties are not compromised. All cable lifelines are a 0.188" (5 mm) galvanized wire cable for optimal durability against high heat, abrasion, and hazardous environments. All devices incorporate a double locking snap hook that swivels 360 degrees with a built-in fall indicator. CSA certified. Meets and exceeds ANSI and OSHA regulations. RATED FOR 310 LB WEIGHT CAPACITY.

Self-Retracting Lifelines Class SRL


PART NO	LIFELINE MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP2YY11C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	11 FT (3.4 M)
FP2YY15C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	15 FT (4.6 M)
FP2AA06C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	TRIPLE ACTION CARABINER	20 FT (6.1 M)
FP2YY30C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	30 FT (9 M)
FP2AA10C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	32.5 FT (10 M)
FP2AA15C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	50 FT (15 M)
FP2YY50C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	50 FT (15 M)
FP2YY65C	GALVANIZED CABLE	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	65 FT (20 M)

Please refer to page 34 for hardware details.

Swivel Hook: FP4651 | Triple Action Carabiner: FP244



Rope & Web Lanyards



FP61111



FP61114



FP63101



FP63111



FP63213



FP635133



FP63118



FP641E7

3-Strand Nylon Rope Lanyard

This type of lanyard is almost exclusively used for travel restraint.

PART NO	LANYARD MATERIAL	HARNESSE CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP61111	3-STRAND NYLON OF (0.625") 16 MM	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP61113	3-STRAND NYLON OF (0.625") 16 MM	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP61114	3-STRAND NYLON OF (0.625") 16 MM	SMALL HOOK	LARGE HOOK	4-5-6 FT

Fixed and Adjustable Length Web Lanyards Without Energy Absorbers

This lanyard is designed for travel restraint.

PART NO	LANYARD MATERIAL	HARNESSE CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG FIXED LANYARDS				
FP63101	1 IN WIDE POLYESTER WEB	SEWN LOOP	SMALL HOOK	4-5-6 FT
FP63111	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP63113	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP63114	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK	4-5-6 FT
FP6311H	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK	4-5-6 FT
SINGLE LEG ADJUSTABLE LANYARDS				
FP63211	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK	3.5 TO 6 FT
FP63213	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK	3.5 TO 6 FT
FP63214	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK	3.5 TO 6 FT
FP6321H	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK	3.5 TO 6 FT
DOUBLE LEG FIXED Y-LANYARDS				
FP635111	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FP635133	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FP635144	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FP6351HH	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK (2)	4-5-6 FT
DOUBLE LEG ADJUSTABLE Y-LANYARDS				
FP63D111	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK (2)	3.5 TO 6 FT
FP63D133	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK (2)	3.5 TO 6 FT
FP63D144	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK (2)	3.5 TO 6 FT
FP63D1HH	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK (2)	3.5 TO 6 FT


Removable Extended Back D-Ring

PART NO	LANYARD MATERIAL	HARNESSE CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP63118	1 IN WIDE POLYESTER WEB	SMALL HOOK	3 IN O-RING	2 FT
FP641E7	1 IN WIDE POLYESTER WEB	LOOP	SMALL D-RING	18"

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS

Dyna-One™ Lanyards



FP7331



FP733AC



FP73413



FP736111



FP736144



FP736ACC



FP7431



FP746144

Designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb). It is very important for the user to calculate the fall clearance requirement when using a lanyard with an energy absorber. (See calculations on page 43).

Lanyards Fixed Length with Dyna-One™ Energy Absorber


PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FP73311	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP73313	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP73314	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK	4-5-6 FT
FP7331H	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK	4-5-6 FT
FP733AA	1 IN WIDE POLYESTER WEB	ALUM SMALL HOOK	ALUM SMALL HOOK	4-5-6 FT
FP733AC	1 IN WIDE POLYESTER WEB	ALUM SMALL HOOK	ALUM LARGE HOOK	4-5-6 FT
SINGLE LEG ADJUSTABLE LANYARD WITH ENERGY ABSORBER				
FP73411	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK	3.5 TO 6 FT
FP73413	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK	3.5 TO 6 FT
FP73414	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK	3.5 TO 6 FT
FP7341H	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK	3.5 TO 6 FT
DOUBLE LEG Y-LANYARD WITH ENERGY ABSORBER				
FP736111	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FP736133	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FP736144	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FP7361HH	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK (2)	4-5-6 FT
FP736AAA	1 IN WIDE POLYESTER WEB	ALUM SMALL HOOK	ALUM SMALL HOOK (2)	4-5-6 FT
FP736ACC	1 IN WIDE POLYESTER WEB	ALUM SMALL HOOK	ALUM LARGE HOOK (2)	4-5-6 FT
DOUBLE LEG ADJUSTABLE Y-LANYARD WITH ENERGY ABSORBER				
FP737111	1 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK (2)	3.5 TO 6 FT
FP737133	1 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK (2)	3.5 TO 6 FT
FP737144	1 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK (2)	3.5 TO 6 FT
FP7371HH	1 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK (2)	3.5 TO 6 FT
FIXED & CONTINUOUS SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FP74311	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP74313	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP74314	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK	4-5-6 FT
FP7431H	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK	4-5-6 FT
FIXED & CONTINUOUS Y-LANYARD WITH ENERGY ABSORBER				
FP746111	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FP746133	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FP746144	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FP7461HH	1.75 IN WIDE POLYESTER WEB	SMALL HOOK	X LARGE HOOK (2)	4-5-6 FT

Please refer to page 34 for hardware details.

Small Hook: FP665OHS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP665OALL | **Aluminum Large:** FP5395ALL



Dyna-Lite™ Lanyards



FP743226



FP7462666



FP743266

Economy lanyards designed to reduce the impact load experienced during a fall. CSA certified. Meets and exceeds ANSI and OSHA regulations. Specifically designed for fall arrest, with Dyna-One™ energy absorber rated for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).


Fixed Web Lanyard with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG FIXED LANYARD				
FP743226	1 IN POLYESTER WEBBING	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP743266	1 IN POLYESTER WEBBING	SMALL HOOK	LARGE HOOK	4-5-6 FT
DOUBLE LEG FIXED LANYARD				
FP7462666	1 IN POLYESTER WEBBING	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS

Dyna-Yard™ Lanyards



FP75811



FP75814

A tubular lanyard designed to reduce impact load experienced during a fall. CSA certified. Meets and exceeds ANSI and OSHA regulations. Specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).

Dyna-Yard™ Lanyard with Integrated Dyna-One™ Energy Absorber


PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP75811	POLYESTER	SMALL HOOK	SMALL HOOK	6 FT
FP75813	POLYESTER	SMALL HOOK	MEDIUM HOOK	6 FT
FP75814	POLYESTER	SMALL HOOK	LARGE HOOK	6 FT
FP7581H	POLYESTER	SMALL HOOK	X LARGE HOOK	6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL

Cable Dyna-One™ Lanyards

Kevlar® Lanyards



FP76311




FP766144


The PVC coating provides additional durability to withstand harsh conditions, making it versatile in a wider array of applications. Flemish eyes termination on the cable provides additional safety to ensure that the product will perform when required. CSA certified. Meets and exceeds ANSI and OSHA regulations. Specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).

Lanyards Fixed Length with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL WITH PVC COATING	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FP76311	.25 IN STEEL CABLE	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP76313	.25 IN STEEL CABLE	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP76314	.25 IN STEEL CABLE	SMALL HOOK	LARGE HOOK	4-5-6 FT
FP7631H	.25 IN STEEL CABLE	SMALL HOOK	X LARGE HOOK	4-5-6 FT
FP763AA	.25 IN STEEL CABLE	ALUM SMALL HOOK	ALUM SMALL HOOK	4-5-6 FT
FP763AC	.25 IN STEEL CABLE	ALUM SMALL HOOK	ALUM LARGE HOOK	4-5-6 FT
DOUBLE LEG Y-LANYARD WITH ENERGY ABSORBER				
FP766111	.25 IN STEEL CABLE	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FP766133	.25 IN STEEL CABLE	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FP766144	.25 IN STEEL CABLE	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FP7661HH	.25 IN STEEL CABLE	SMALL HOOK	X LARGE HOOK (2)	4-5-6 FT
FP766AAA	.25 IN STEEL CABLE	ALUM SMALL HOOK	ALUM SMALL HOOK (2)	4-5-6 FT
FP766ACC	.25 IN STEEL CABLE	ALUM SMALL HOOK	ALUM LARGE HOOK (2)	4-5-6 FT



FP786111



FP78313

Manufactured from Kevlar® webbing to provide exceptional protection against cuts and abrasions, as well as high heat resistance to sparks and flames, along with the security of maximum protection in case of a fall. Meets and exceeds ASTM F887 Arc Flash requirements and is CSA certified. Meets and exceeds ANSI and OSHA regulations. These energy absorbers come protected inside a leather pouch. This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).

Kevlar® Lanyards with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL WITH PVC COATING	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FP78301	KEVLAR®	SOFT LOOP	SMALL HOOK	4-5-6 FT
FP78303	KEVLAR®	SOFT LOOP	MEDIUM HOOK	4-5-6 FT
FP78304	KEVLAR®	SOFT LOOP	LARGE HOOK	4-5-6 FT
FP7830H	KEVLAR®	SOFT LOOP	X LARGE HOOK	4-5-6 FT
FP78311	KEVLAR®	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP78313	KEVLAR®	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP78314	KEVLAR®	SMALL HOOK	LARGE HOOK	4-5-6 FT
FP7831H	KEVLAR®	SMALL HOOK	X LARGE HOOK	4-5-6 FT
DOUBLE LEG Y-LANYARD WITH ENERGY ABSORBER				
FP786111	KEVLAR®	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FP786133	KEVLAR®	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FP786144	KEVLAR®	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FP7881HH	KEVLAR®	SMALL HOOK	X LARGE HOOK (2)	4-5-6 FT

Leather Cover Replacement


PART NO	DESCRIPTION
FPLANCOVER	LEATHER COVER TO PROTECT THE ENERGY ABSORBER

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL



Tower Lanyards



FP734AAR



FP737ACCR

Specifically designed for the tower industry due to its aluminum snap hooks which keep it lightweight. There is an O-ring to be used for tieback around the structure and can be used for rescue situations. The lanyard leg is adjustable to accommodate different size anchor structures.


Tower Lanyards with O-Ring for Rescue

PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG ADJUSTABLE LENGTH LANYARD WITH ENERGY ABSORBER				
FP734AAR	POLYESTER	ALUM SMALL HOOK	ALUM SMALL HOOK	6 FT
FP734ACR	POLYESTER	ALUM SMALL HOOK	ALUM LARGE HOOK	6 FT
DOUBLE LEG Y-LANYARD ADJUSTABLE LENGTH WITH INTEGRATED ENERGY ABSORBER				
FP737AAAR	POLYESTER	ALUM SMALL HOOK	ALUM SMALL HOOK (2)	6 FT
FP737ACCR	POLYESTER	ALUM SMALL HOOK	ALUM LARGE HOOK (2)	6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL

Coated Lanyards



FPC74311



FPC746144

Ideal for dirty, contaminated or clean environments. The TPU coating provides resistance to abrasions, weld splatter, chemicals, paint, grease, and dirt. The lanyard leg can be wiped clean, making it easier to inspect and reducing the frequency of replacement. CSA certified. Meets and exceeds ANSI and OSHA regulations. This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).


Coated Lanyards with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FPC74311	COATED POLYESTER	SMALL HOOK	SMALL HOOK	4-5-6 FT
FPC74313	COATED POLYESTER	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FPC74314	COATED POLYESTER	SMALL HOOK	LARGE HOOK	4-5-6 FT
FPC7431H	COATED POLYESTER	SMALL HOOK	X LARGE HOOK	4-5-6 FT
FPC743AA	COATED POLYESTER	ALUM SMALL HOOK	ALUM SMALL HOOK	4-5-6 FT
FPC743AC	COATED POLYESTER	ALUM SMALL HOOK	ALUM LARGE HOOK	4-5-6 FT
DOUBLE LEG Y-LANYARD WITH ENERGY ABSORBER				
FPC746111	COATED POLYESTER	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FPC746133	COATED POLYESTER	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FPC746144	COATED POLYESTER	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FPC7461HH	COATED POLYESTER	SMALL HOOK	X LARGE HOOK (2)	4-5-6 FT
FPC746AAA	COATED POLYESTER	ALUM SMALL HOOK	ALUM SMALL HOOK (2)	4-5-6 FT
FPC746ACC	COATED POLYESTER	ALUM SMALL HOOK	ALUM LARGE HOOK (2)	4-5-6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Large: FP5395ALL | **Aluminum Large:** FP5395ALL

Stretch Lanyards



FP7S311

This lanyard's leg stretches from a length of 4.5 ft to 6 ft which allows the lanyard to stay out of the way when not in use, while providing the freedom to move away from your anchor point when required. This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).


Stretch Lanyards with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FP7S311	POLYESTER	SMALL HOOK	SMALL HOOK	4.5 TO 6 FT
FP7S313	POLYESTER	SMALL HOOK	MEDIUM HOOK	4.5 TO 6 FT
FP7S314	POLYESTER	SMALL HOOK	LARGE HOOK	4.5 TO 6 FT
FP7S31H	POLYESTER	SMALL HOOK	X LARGE HOOK	4.5 TO 6 FT
FP7S3AA	POLYESTER	ALUM SMALL HOOK	ALUM SMALL HOOK	4.5 TO 6 FT
FP7S3AC	POLYESTER	ALUM SMALL HOOK	ALUM LARGE HOOK	4.5 TO 6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL

Anti-Corrosion Lanyards



FP743FG

Designed with aluminum carabiners which will perform better in corrosive environments. This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).

Anti-Corrosion Lanyards with Dyna-One™ Energy Absorber


PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP743FG	POLYESTER	ALUM CARABINER	LARGE ALUM CARABINER	4-5-6 FT
FP746FGG	Y-LANYARD POLYESTER	ALUM CARABINER	LARGE ALUM CARABINER	4-5-6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL



Reflective Lanyards



FP7R311



FP7R313

Features 0.5" (12.7 mm) reflective strip on 1.75" (45 mm) web lanyard with Dyna-One™ energy absorber. This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).


Reflective Lanyards with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER				
FP7R311	POLYESTER	SMALL HOOK	SMALL HOOK	4-5-6 FT
FP7R313	POLYESTER	SMALL HOOK	MEDIUM HOOK	4-5-6 FT
FP7R314	POLYESTER	SMALL HOOK	LARGE HOOK	4-5-6 FT
FP7R31H	POLYESTER	SMALL HOOK	XLARGE HOOK	4-5-6 FT
DOUBLE LEG LANYARD WITH INTEGRATED ENERGY ABSORBER				
FP7R6111	POLYESTER	SMALL HOOK	SMALL HOOK (2)	4-5-6 FT
FP7R6133	POLYESTER	SMALL HOOK	MEDIUM HOOK (2)	4-5-6 FT
FP7R6144	POLYESTER	SMALL HOOK	LARGE HOOK (2)	4-5-6 FT
FP7R61HH	POLYESTER	SMALL HOOK	XLARGE HOOK (2)	4-5-6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL

Tie-Back Lanyards



FP7331T



FP7371TT

Tie-back lanyards provide the ability to wrap the lanyard leg around a structure and connect back to itself. An auto-lock snap hook with 5,000 lb gate strength ensures there are no accidental disconnections. Eliminates the need for an additional anchorage connector. Specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).


Tie-Back Lanyards with Dyna-One™ Energy Absorber

PART NO	LANYARD MATERIAL	TYPE	HARNESS CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
SINGLE LEG LANYARD WITH ENERGY ABSORBER					
FP7331T	POLYESTER	FIXED	SMALL HOOK	TIE-BACK SMALL HOOK	4-5-6 FT
FP7341T	POLYESTER	ADJUSTABLE	SMALL HOOK	TIE-BACK SMALL HOOK	3.5 TO 6 FT
DOUBLE LEG Y-LANYARD WITH ENERGY ABSORBER					
FP7361TT	POLYESTER	FIXED	SMALL HOOK	TIE-BACK SMALL HOOK (2)	4-5-6 FT
FP7371TT	POLYESTER	ADJUSTABLE	SMALL HOOK	TIE-BACK SMALL HOOK (2)	3.5 TO 6 FT

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS
Aluminum Small: FP6650ALL | **Aluminum Large:** FP5395ALL

Dyna-One™ Energy Absorbers and Extended D-Ring



FP70311



FP70377



FP70399

This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).


Dyna-One™ Energy Absorber with Connectors

PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
DYNA-ONE™ ENERGY ABSORBER				
FP70311	POLYESTER	SMALL HOOK	SMALL HOOK	18 IN
FP70391	POLYESTER	SMALL HOOK	LARGE D-RING	18 IN
FP70377	POLYESTER	SMALL D-RING	SMALL D-RING	13.5 IN
FP70399	POLYESTER	LARGE D-RING	LARGE D-RING	16.5 IN
FP703E1	POLYESTER	LOOP	SMALL HOOK	16.5 IN
FP703E9	POLYESTER	LOOP	LARGE D-RING	16.5 IN

Please refer to page 34 for hardware details.

Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS

Work Positioning Products



FP675113



FP635113



FPPOLEST



FPADRL

Rebar Chain Assemblies

PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP635113	POLYESTER	SMALL HOOK (2)	LARGE HOOK	22"
FP675113	STEEL CHAIN	SMALL HOOK (2)	LARGE HOOK	28"

Pole Starp

PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FPPOLEST	POLYESTER	SMALL HOOK	SMALL HOOK	3-4 FT

Adjustable Rope Pole Positioning lanyard


PART NO	LANYARD MATERIAL	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FPADRL	KERNMANTLE	0.75" ALUMINUM CARABINER	ALUMINUM ROPE ADJUSTER	8 FT

Please refer to page 34 for hardware details.


Small Hook: FP6650HS | **Medium Hook:** FP5386HS | **Large Hook:** FP5395HS | **XL Hook:** FP3680TS




Hooks & Carabiners



FP6650HS




FP4651



FP9652HS




FP5386HS



FP5395HS



FP5395ALL



FP3680TS



FP415



FP843



FP714



FP775



FP244



FP261



FP731
(SHOWN ON FP244)



FPSRLTNCON

Hooks and carabiners designed for a multitude of applications, and all are available in various forms and sizes. They offer maximum protection, requiring double-action to unlock as well as auto-locking closures. They are also designed to give you the greatest ease of operation. All are approved for a maximum load of 5,000 lb (22 kN) unless otherwise specified. CSA, ANSI and CE certified.

Double-Action Small Ergonomic Snap Hooks

PART NO	CONSTRUCTION	OPENING	TYPE OF LOCK
FP6650HS	FORGED STEEL	0.8 IN (20 MM)	DOUBLE-ACTION
FP6650ALL	ALUMINUM	0.8 IN (20 MM)	DOUBLE-ACTION
FP4651	FORGED STEEL /SWIVEL	0.8 IN (20 MM)	DOUBLE-ACTION
FP9652HS	STAMPED STEEL	0.8 IN (20 MM)	DOUBLE-ACTION

Double-Action Large Snap Hooks

PART NO	CONSTRUCTION	OPENING	TYPE OF LOCK
FP5386HS	FORGED STEEL	2 IN (50 MM)	DOUBLE-ACTION
FP3680TS	FORGED STEEL	3.2 IN (81 MM)	DOUBLE-ACTION
FP5395HS	FORGED STEEL	2.5 IN (64 MM)	DOUBLE-ACTION
FP5395ALL	ALUMINUM	2.5 IN (64 MM)	DOUBLE-ACTION
FP5386ALL	ALUMINUM	2 IN (50 MM)	DOUBLE-ACTION


Twist Lock Carabiner Connector

PART NO	CONSTRUCTION	OPENING	TYPE OF LOCK
FP715	ALLOY STEEL & HEAT TREATED "D" SHAPE	0.625 IN (16 MM)	AUTO-TWIST LOCK
FP415ALL	ALUMINUM "D" SHAPE	0.625 IN (16 MM)	AUTO-TWIST LOCK
FP244	ALLOY STEEL & HEAT TREATED "D" SHAPE	0.75 IN (19 MM)	AUTO-TWIST LOCK TRIPLE ACTION
FP415	ALLOY STEEL & HEAT TREATED "D" SHAPE	0.75 IN (19 MM)	AUTO-TWIST LOCK
FP843	ALLOY STEEL & HEAT TREATED "D" SHAPE	0.75 IN (19 MM)	AUTO-TWIST LOCK
FP775	ALLOY STEEL & HEAT TREATED "D" SHAPE	1 IN (25 MM)	AUTO-TWIST LOCK
FP775ALL	ALUMINUM "D" SHAPE	1 IN (25 MM)	AUTO-TWIST LOCK
FP714	ALLOY STEEL & HEAT TREATED PEAR SHAPE	2.25 IN (57 MM)	AUTO-TWIST LOCK
FP714ALL	ALUMINUM PEAR SHAPE	2.25 IN (57 MM)	AUTO-TWIST LOCK

Dual Self-Retracting Lifeline Hardware

PART NO	DESCRIPTION
FP731	PLASTIC SEPARATOR FOR DUAL SELF-RETRACTING DEVICES
FPSRLTNCON	STEEL CONNECTOR FOR DUAL SELF-RETRACTING LIFELINES

Vertical Rope Lifelines



FP16KRN25



FP58EPS25




FP16EPS25



FP16EPS25A



FP16EPS25B



FP16EPS25C

Vertical lifelines come with different materials which will range in durability. They are also available in different lengths and various anchor hardware. Our vertical rope lifelines meet and exceed ANSI and OSHA, and are CSA certified only when used with Dynamic® rope grabs.


Lanyards Fixed Length with Dyna-One™ Energy Absorber

PART NO	MATERIAL	CONNECTORS	LENGTH
FP16KRN25	KERMANTLE ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	25 FT (7.6 M)
FP16KRN50	KERMANTLE ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	50 FT (15.2 M)
FP16KRN100	KERMANTLE ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	100 FT (30.5 M)
FP58EPS25	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	25 FT (7.6 M)
FP58EPS50	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	50 FT (15.2 M)
FP16EPS25	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	25 FT (7.6 M)
FP16EPS50	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	50 FT (15.2 M)
FP16EPS75	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	75 FT (22.8 M)
FP16EPS100	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 CARABINER FP415	100 FT (30.5 M)
FP16EPS25A	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 SMALL HOOK 6650HS	25 FT (7.6 M)
FP16EPS50A	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 SMALL HOOK 6650HS	50 FT (15.2 M)
FP16EPS75A	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 SMALL HOOK 6650HS	75 FT (22.8 M)
FP16EPS100A	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 SMALL HOOK 6650HS	100 FT (30.5 M)
FP16EPS25B	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 MEDIUM HOOK FP5386HS	25 FT (7.6 M)
FP16EPS50B	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 MEDIUM HOOK FP5386HS	50 FT (15.2 M)
FP16EPS75B	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 MEDIUM HOOK FP5386HS	75 FT (22.8 M)
FP16EPS100B	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 MEDIUM HOOK FP5386HS	100 FT (30.5 M)
FP16EPS25C	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 LARGE HOOK FP5395HS	25 FT (7.6 M)
FP16EPS50C	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 LARGE HOOK FP5395HS	50 FT (15.2 M)
FP16EPS75C	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 LARGE HOOK FP5395HS	75 FT (22.8 M)
FP16EPS100C	3-STRAND CO-POLYMER BLEND ROPE 0.625 IN (16 MM)	1 TERMINATION & 1 LARGE HOOK FP5395HS	100 FT (30.5 M)

NOTE: Other configurations of vertical lifelines also available. See our price list for more details.
All our vertical lifelines are shrink wrapped at both spliced termination ends.



Rope Grabs

 CERTIFIED



FP13130

Rope grab kits offer a practical solution for many fall arrest applications. Rope grabs are equipped with a Panic Lock feature as well as an orientation lock-out feature that will not allow the rope grab to be installed upside down. All our rope grab combinations Meet and exceed ANSI and OSHA and are CSA certified only when used with Dynamic® Vertical Lifelines. This lanyard is specifically designed for fall arrest purposes for workers weighing between 45 kg (100 lb) to 140 kg (310 lb).



FP15130

Rope Grabs

PART NO	DESCRIPTION
FP13130	AUTOMATIC ROPE GRAB WITH PANIC LOCK (LARGE EYE) WITH 30 IN (0.8 M) DYNA-ONE™ ENERGY ABSORBING LANYARD & 1 DOUBLE LOCKING ERGONOMIC SMALL HOOK FP6650HS
FP15130	AUTOMATIC ROPE GRAB WITH PANIC LOCK (LARGE EYE) WITH 30 IN (0.8 M) LANYARD & 1 DOUBLE LOCKING ERGONOMIC SMALL HOOK FP6650HS

Anchorage Connectors



FP10



FP10F



FP12



FP103FD



FP11



FP151.4



FP163.5



FP13

Anchorage slings are easy to use and versatile for many applications where you can wrap around the supporting structure. Each has a minimum tensile strength of 5,000 lb (22 kN).

Anchorage Connectors

PART NO	DESCRIPTION	LENGTH
FP10	CABLE SLING .25" (6 MM) GALVANIZED STEEL CLEAR PVC COATED AGAINST CORROSION SWAGED EYES AT EACH END.	3 FT (0.9 M) - 4 FT (1.2 M) 5 FT (1.5 M) - 6 FT (1.8 M)
FP10F	CABLE SLING .25" (6 MM) GALVANIZED STEEL RED PVC COATED AGAINST CORROSION FLEMISH EYE SPLICE AT EACH END.	3 FT (0.9 M) - 4 FT (1.2 M) 5 FT (1.5 M) - 6 FT (1.8 M)
FP103FC	CABLE SLING CHOKER .25" (6 MM) GALVANIZED CABLE WITH PVC COATED FLEMISH EYE AT BOTH ENDS. ONE O-RING OF 2" (50 MM) AT ONE END AND ONE O-RING OF 3" (76 MM) AT THE OTHER END. THE 2" TO BE SLID IN THE 3" TO CREATE THE CHOKER.	3 FT (0.9 M) - 4 FT (1.2 M) 5 FT (1.5 M) - 6 FT (1.8 M)
FP103FD	CABLE SLING CHOKER .25" (6 MM) GALVANIZED CABLE WITH PVC COATED FLEMISH EYE AT BOTH ENDS. ONE O-RING OF 3" (76 MM) AT ONE END AND ONE SMALL HOOK FP6650HS AT THE OTHER END. THE SMALL HOOK TO BE SLID INTO THE 3" TO CREATE THE CHOKER.	3 FT (0.9 M) - 4 FT (1.2 M) 5 FT (1.5 M) - 6 FT (1.8 M)
FP103FE	CABLE SLING CHOKER .25" (6 MM) GALVANIZED CABLE WITH PVC COATED FLEMISH EYE AT BOTH ENDS. ONE SMALL HOOK FP6650HS AT THE END.	3 FT (0.9 M) - 4 FT (1.2 M) 5 FT (1.5 M) - 6 FT (1.8 M)
FP11	PASS THROUGH ANCHOR SLING 2" (50 MM), POLYESTER WEBBING, ONE SMALL D-RING AND ONE LARGE D-RING.	3 FT (0.9 M) - 4 FT (1.2 M) 6 FT (1.8 M)
FP12	CROSS ARM ANCHOR SLING 2" (50 MM), POLYESTER WEBBING WITH SEWN LOOP AND ONE LARGE D-RING THAT PASSES THROUGH THE LOOP TO TIGHTEN AROUND AN ANCHOR POINT.	3 FT (0.9 M) - 4 FT (1.2 M) 6 FT (1.8 M)
FP13	RESIDENTIAL ANCHOR SLING. HEAVY DUTY POLYESTER WEBBING.	3 FT (0.9 M)
FP151.4	SCAFFOLD ANCHOR SLING 2" (50 MM) NYLON WEBBING WITH SEWN LOOP AND ONE LARGE D-RING.	17 IN (0.4 M)
FP163.5	DISPOSABLE IMPORTED ANCHOR SLING WITH PROTECTIVE SLEEVE.	3.5 FT (1 M)
FP173	DISPOSABLE ANCHOR SLING WITH SEWN LOOPS ON EACH END.	3 FT (0.9 M)
FP183	SEWN CIRCLE WITH D-RING ANCHOR SLING.	3 FT (0.9 M)
FP194	DISPOSABLE ANCHOR SLING WITH D-RING.	4 FT (1.2 M)



FP173



FP183



Anchorage Connectors



FP3730



FP373410Y



FP373375



FP3731



FP3732414



FP3732V414



FP37345S



FP3800

Various Anchorage Connectors

PART NO	DESCRIPTION	STRUCTURE TYPE
FP3730	D-RING ANCHORAGE CONNECTOR 0.75" (19 MM) HOLE	STEEL / CONCRETE
FP373175	TEMPORARY REMOVABLE CONCRETE ANCHOR. 0.75" (19 MM), DIAMETER RATED FOR 22 KN (5,000 LB)	CONCRETE
FP37311	TEMPORARY REMOVABLE CONCRETE ANCHOR. 1" (25 MM), DIAMETER RATED FOR 44 KN (10,000 LB)	CONCRETE
FP3731M15	TEMPORARY AND REMOVABLE MINING BOLT ANCHOR FOR 1.5" (39 MM) HOLES. RATED FOR 44 KN (10,000 LB)	ROCK
FP373375	TEMPORARY REMOVABLE TOGGLE ANCHOR THAT CAN BE USED ON STEEL OR CONCRETE. 0.75" (19 MM) DIAMETER. RATED FOR 22 KN (5,000 LB)	STEEL / CONCRETE
FP373410Y	SEMI-PERMANENT SWIVEL HYBRID D-RING THAT IS REMOVABLE AND RE-USABLE. 1" (25 MM) DIAMETER. RATED FOR 44 KN (10,000 LB)	CONCRETE


5K Zinc Plated Swivel D-Ring

PART NO	DESCRIPTION	STRUCTURE TYPE
FP37345N	5K ZINC PLATED SWIVEL D-RING WITH NO HARDWARE, 0.625" (16 MM), DIAMETER RATED FOR 22 KN (5,000 LB)	STEEL / CONCRETE
FP37345C	5K ZINC PLATED SWIVEL D-RING WITH CONCRETE HARDWARE, 0.625" (16 MM), DIAMETER RATED FOR 22 KN (5,000LB)	CONCRETE
FP37345S	5K ZINC PLATED SWIVEL D-RING WITH STEEL HARDWARE, 0.625" (16 MM), DIAMETER RATED FOR 22 KN (5,000LB)	STEEL
FP37345SB	STEEL HARDWARE ONLY FOR 5K ZINC PLATED SWIVEL D-RING	STEEL
FP37345CB	CONCRETE HARDWARE ONLY FOR 5K ZINC PLATED SWIVEL D-RING	CONCRETE

Beam Anchors

PART NO	DESCRIPTION	STRUCTURE TYPE
FP3732414	BEAM CLAMP EASY SLIDER FOR I-BEAM WITH 4-14" (100-356 MM) WIDTH	STEEL I-BEAM
FP3732V414	VERTICAL BEAM CLAMP EASY SLIDER FOR I-BEAM WITH 4-14" (100-356 MM) WIDTH	STEEL I-BEAM
FP37321230	BEAM CLAMP EASY SLIDER FOR I-BEAM WITH 12-30" (305-762 MM) WIDTH	STEEL I-BEAM
FP3800	BEAM TROLLEY WITH WHEELS FOR I-BEAMS WITH 3-10" (76-254 MM) WIDTH	STEEL I-BEAM

Door | Window Anchor



FP960

Door | Window Anchor

PART NO	DESCRIPTION
FP960	PROVIDES A NON-INTRUSIVE ANCHOR POINT AND CAN BE EASILY INSTALLED INSIDE THE INTERIOR OF A DOOR FRAME OR WINDOW OPENING ENABLING THE MOST DIFFICULT JOB TO GET DONE SAFELY. ADJUSTABLE FROM 23.62" TO 49.12" (59.05 CM TO 123.02 CM). STORAGE BAG INCLUDED

Roof Brackets



FP09D




FP09R

Roof Brackets

PART NO	DESCRIPTION
FP09D	DISPOSABLE ROOF ANCHOR (WITH NAILS)
FP09R	REUSABLE ROOF ANCHOR (WITH SCREWS)
FP09RF	REUSABLE FLAT ROOF ANCHOR (WITH SCREWS)

4 Persons Temporary Rope Horizontal Lifeline



FP3001

4 Persons Temporary Rope Horizontal Lifeline

PART NO	DESCRIPTION
FP3001	ADJUSTABLE HORIZONTAL LIFELINE THAT SPANS 16 FT (5 M) TO 82 FT (25 M), SUITABLE FOR 4 PERSONS. INCLUDES 0.625" (16 MM) DIAMETER KERNMANTLE ROPE, CORROSION RESISTANT TENSIONER, 4 STEEL O-RINGS FOR THE USER TO EASILY ATTACH HIS LANYARD TO AND CARABINER END CONNECTIONS.

Rescue and Retrieval Systems



FPWORKSEAT



FP4017B



FPWRISTLETS



FPTRAUST

Rescue and Retrieval Systems

PART NO	DESCRIPTION
FP4017B	SPREADER BAR
FPWRISTLETS	WRISTLETS
FPTRAUST	TRAUMA STRAPS
FPWORKSEAT	WORK SEAT FOR EXTENDED WORKING AT HEIGHTS




Tripods and Accessories



FP09907 / FP09910
WITH FP3AA15CR



FP099073



FP860



FP3AA15CR

Versatile and lightweight tripods made of high-strength aluminum, with adjustable legs. Legs can be independently locked in place and feature spiked feet for slippery surfaces. Accessories mounted on the outside to maximize work/rescue area under the tripod. Available in 7 ft (2 m) and 9 ft (3 m) configurations. Withstands up to 5,000 lb (22 kN). Maximum worker weight capacity of 400 lb. Meets and exceeds all applicable ANSI and CSA standards.

Tripods and Tripod Kits

PART NO	DESCRIPTION
FP09907	7 FT (2 M) TRIPOD WITH TELESCOPING LEGS THAT CAN ADJUST FROM 4 FT TO 7 FT. ALUMINUM CONSTRUCTION AND STEEL FEET WITH SPIKES FOR SLIPPERY SURFACES
FP09910	9 FT (3 M) TRIPOD WITH TELESCOPING LEGS THAT CAN ADJUST FROM 7.5 FT TO 9 FT. ALUMINUM CONSTRUCTION AND STEEL FEET WITH SPIKES FOR SLIPPERY SURFACES
FP09907AK3W	TRIPOD KIT WHICH INCLUDES FP09907 7 FT (2 M) TRIPOD, FP09907/3 DEVICE BRACKET, FP3AA15CR 3-WAY SELF-RETRACTING LIFELINE, AND FP1007 BAG

Tripod Device Brackets

PART NO	DESCRIPTION
FP09907/1	TRIPOD DEVICE BRACKET DESIGNED FOR FP3NN50CR SELF-RETRACTING LIFELINE 3-WAY DEVICE
FP09907/2	TRIPOD DEVICE BRACKET DESIGNED FOR FP3NN85CR SELF-RETRACTING LIFELINE 3-WAY DEVICE
FP09907/3	TRIPOD DEVICE BRACKET DESIGNED FOR FP3AA15CR SELF-RETRACTING LIFELINE 3-WAY DEVICE
FP09907/4	TRIPOD DEVICE BRACKET DESIGNED FOR FP3AA33CR SELF-RETRACTING LIFELINE 3-WAY DEVICE

Accessories for Tripod

PART NO	DESCRIPTION
FP099HDPINS	PIN FOR TRIPOD HEAD
FP099RING	TRIPOD O-RING
FP099PULLEY	TRIPOD PULLEY ASSEMBLY
FPTRIPDST7	STRAP FOR 7 FT (2 M) TRIPOD
FPTRIPDST9	STRAP FOR 9 FT (3 M) TRIPOD
FP099FEET	TRIPOD FEET
FP099PLPIN	PIN FOR TRIPOD HEAD PULLEY
FP099LGPIN	PIN FOR TRIPOD LEG
FP099BRPIN	PIN FOR DEVICE BRACKETS
FP099BRBOLT	BOLT FOR DEVICE BRACKETS

Winch

Winch to be used for raising or lowering of personel or material in confined spaces. Equipped with a mounting plate that connects to the tripod. Galvanized Steel wire rope of 0.19 in (5 mm) dia. Maximum lifting load capacity of 300 lb (136 kg). Comes with a snap hook model FP6650 as a connector.

PART NO	DESCRIPTION
FP860	WINCH WITH GALVANISED STEEL CABLE AND SMALL HOOK, 60 FT (18 M)
FP860B	WINCH BRACKET REPLACEMENT FOR FP860

Self-Retracting Lifelines with Integrated Retrieval Winch Class SRL-R

PART NO	LIFELINE MATERIAL	RETRIEVAL WINCH	HARNES CONNECTOR	ANCHORAGE CONNECTOR	LENGTH
FP3AA15CR	GALVANIZED CABLE	3 WAY	SWIVEL HOOK (W/ LOAD INDICATOR)	CARABINER	50 FT (15 M)

Compliance Kits



FPKIT016U

Roofer's Kits



FPRK09825



FPRK099DL25



FPRK09925B



FPRK09925D



FPRK099Y50

Compliance Kits

Basic "B-Compliant" Kits in Bag

PART NO	DESCRIPTION	SIZE OF HARNESS	LENGTH OF ROPE
FPKIT016U	BASIC KIT INCL: (1) FP4101DU HARNESS WITH PERMANENTLY 6 FT (1.8 M) ATTACHED FP743226 LANYARD, (1) FP1002 EQUIPMENT BAG.	UNIVERSAL	6 FT (1.83 M)
FPKIT5P6U	BASIC KIT INCL: (1) FP2601DU HARNESS WITH PERMANENTLY 6 FT (1.8 M) ATTACHED FP743226 LANYARD, (1) FP1002 EQUIPMENT BAG.	UNIVERSAL	6 FT (1.83 M)

Roofer's Kits

"B-Compliant" Deluxe Roofer's Kits in Storage Bucket

PART NO	DESCRIPTION	SIZE OF HARNESS	LENGTH OF ROPE
FPRK099DL25	ROOFER'S KIT INCL: (1) FP16KRN25 LIFELINE, (1) FP2501DXL HARNESS, (1) ROPE GRAB FP13130 WITH 30" (0.8 M) LANYARD AND DYNA-ONE™ ENERGY ABSORBER, (1) REUSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	XL	25 FT (7.6 M)
FPRK099DL50	ROOFER'S KIT INCL: (1) FP16KRN50 LIFELINE, (1) FP2501DXL HARNESS, (1) ROPE GRAB FP13130 WITH 30" (0.8 M) LANYARD AND DYNA-ONE™ ENERGY ABSORBER, (1) REUSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	XL	50 FT (15 M)

"B-Compliant" Econo Roofer's Kits in Storage Bucket

PART NO	DESCRIPTION	SIZE OF HARNESS	LENGTH OF ROPE
FPRK09825	ROOFER'S KIT INCL: (1) FP16EPS25 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP15130 WITH 30" (0.8 M) WEB, (1) DISPOSABLE ROOF ANCHOR FP09D WITH NAILS AND (1) STORAGE BUCKET.	UNIVERSAL	25 FT (7.6 M)
FPRK098R25	ROOFER'S KIT INCL: (1) FP16EPS25 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP15130 WITH 30" (0.8 M) WEB, (1) DISPOSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	UNIVERSAL	25 FT (7.6 M)
FPRK09850	ROOFER'S KIT INCL: (1) FP16EPS50 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP15130 WITH 30" (0.8 M) WEB, (1) DISPOSABLE ROOF ANCHOR FP09D WITH NAILS AND (1) STORAGE BUCKET.	UNIVERSAL	50 FT (15 M)
FPRK098R50	ROOFER'S KIT INCL: (1) FP16EPS50 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP15130 WITH 30" (0.8 M) WEB, (1) REUSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	UNIVERSAL	50 FT (15 M)
FPRK09925B	ROOFER'S KIT INCL: (1) FP16EPS25 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP13130 WITH 2.5 FT (0.8 M) DYNA-ONE™ ENERGY ABSORBING LANYARD, (1) DISPOSABLE ROOF ANCHOR FP09D WITH NAILS AND (1) STORAGE BUCKET.	UNIVERSAL	25 FT (7.6 M)
FPRK09950B	ROOFER'S KIT INCL: (1) FP16EPS50 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP13130 WITH 2.5 FT (0.8 M) DYNA-ONE™ ENERGY ABSORBING LANYARD, (1) DISPOSABLE ROOF ANCHOR FP09D WITH NAILS AND (1) STORAGE BUCKET.	UNIVERSAL	50 FT (15 M)
FPRK09925D	ROOFER'S KIT INCL: (1) FP16EPS25 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP13130 WITH 30" (0.8 M) DYNA-ONE™ ENERGY ABSORBING LANYARD, (1) REUSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	UNIVERSAL	25 FT (7.6 M)
FPRK09950D	ROOFER'S KIT INCL: (1) FP16EPS50 ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP13130 WITH 30" (0.8 M) DYNA-ONE™ ENERGY ABSORBING LANYARD, (1) REUSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	UNIVERSAL	50 FT (15 M)
FPRK099Y50	PALLET OF IMPORTED ROOFER'S KIT INCL: (1) 50 FT (15 M) ECONO LIFELINE, (1) FP4101DU HARNESS, (1) ROPE GRAB FP13130 WITH 30" (0.8 M) DYNA-ONE™ ENERGY ABSORBING LANYARD, (1) REUSABLE ROOF ANCHOR FP09R WITH SCREWS AND (1) STORAGE BUCKET.	UNIVERSAL	50 FT (15 M)



Tool Tethering

Tool Lanyards



Lanyards with Barrel-Lock Carabiner

- ▶ Snag-resistant D frame carabiner with angled gate opening includes a lanyard captive pin for extra security
- ▶ Shock cording inside nylon protective webbing
- ▶ Lock pin on carabiner end for extra security

PART NO	MAX LOAD LIMIT	LEG	CARABINER	GATE OPENING	FASTENER
FP533100011	10 LB (4.5 KG)	SINGLE	BARREL-LOCK	1 IN (2.5 CM)	DRAW STRING
FP533100701	22 LB (9.9 KG)	SINGLE	BARREL-LOCK	1 IN (2.5 CM)	NYLON WEBBING
FP533100012	10 LB (4.5 KG)	DOUBLE	BARREL-LOCK	1.5 IN (3.8 CM)	DRAW STRING



Stretch Tool Lanyard

- ▶ Convenient stretch-lanyard for tool holding
- ▶ Provided with a light-weight carabiner for attachment to the user's belt
- ▶ Max load limit: 22 lb / 9.9 kg
- ▶ Relaxed length: 2.8 ft / 0.9 m
- ▶ Expanded length: 4.4 ft / 1.3 m

PART NO	MAX LOAD LIMIT	LEG	CARABINER	GATE OPENING	FASTENER
FPTOOLTETHER	22 LB (9.9 KG)	SINGLE	SINGLE ACTION	1 IN (2.5 CM)	DRAW STRING

Tool Connector Attachment Points



WEBBING TOOL CONNECTOR

- Premium nylon webbing
- Fully enclosed D-ring for secure attachment
- Swivel head for ease of use with small tools
- Used with tool tape as retrofit tether point for tools/equipment
- Max load limit 3 lb / 1.4kg
- 6 per pack

FP533100352 - 4.5"
FP533100353 - 5.5"



WIRE SLING LOOP

- Loop end to tether tools with small captive holes
- Premium coated stainless steel cable wire
- Max load limit 2 lb / 0.9kg

FP533100801



WIRE SLING WITH SCREW GATE

- Screw gate end to tether tools with small captive holes
- Premium coated stainless steel cable wire
- Max load limit 3 lb / 1.4kg

FP533100802



TOOL BINDING TAPE

- Premium self-adhering tape
- 12 foot roll
- Used with webbing tool connectors as retrofit tether point for tools / equipment
- Max load limit 15 lb / 6.8kg

FP533700101



ELASTICATED CORD TOOL CONNECTOR

- Provides retrofit attachment point to tools / equipment
- Elastic shock cording with barrel lock to attach to tool/equipment
- Swivel head for ease of use
- 3 per pack

FP533100151



Accessories



HARD HAT LANYARD

- High-stretch elastic material
- Easy-to-attach clamp for fabric
- Tethering loop securely connects to hard hat
- Max load limit 2 lb / 0.9kg

FP533300101

Maximum Load Limit
2 lb
0.9 kg



MEASURING TAPE POUCH

- Premium nylon for strength and durability
- Fully enclosed D-ring for secure attachment
- Used to secure most standard tape measures
- Max load limit 2 lb / 0.9kg

FP533300301

Maximum Load Limit
2 lb
0.9 kg



WRISTBAND TOOL HOLDER

- Premium nylon and elastic webbing
- Fully enclosed D-ring for secure attachment
- Shock cording for maximum strength & durability
- Swivel head for easy of use with small tools
- Pull-on design for easy on/off application
- One size fits all
- Max load limit 2 lb / 0.9kg

FP533300401

Maximum Load Limit
2 lb
0.9 kg



UTILITY POUCH

- Premium nylon and elastic webbing
- Fully enclosed D-Ring for secure attachment
- Used to secure radios, cell phones and other small hand tools
- Modular buckle design connects to fall protection and tool belts
- Max load limit 5 lb / 2.3kg

FP533300201

Maximum Load Limit
5 lb
2.3 kg



Tool Tethering Kit

Be confident you have the most common tool tethering safety items you need available in one convenient kit.

STYLE NUMBER	INCLUDES
FP533900101	FP533100011, FP533100352, FP533700101



1x Durable Single-Leg Tool Lanyard
FP533100011




6x 4.5" Webbing Tool Connectors
FP533100352



1x 12-ft Roll of Premium Self-Adhering Tool Binding Tape
FP533700101



Plastic Inspection Tags for Safety Equipment



FPTAGR

Plastic Inspection Tag for Safety Equipment

Durable tag with security locking device, galvanized steel shackle, plastic body with writable area for personal information, a unique serial number to keep track of the product and offered in choice of 5 colors.

PART NO	COLOR	QTY PER PACK
FPTAGR	RED	25
FPTAGB	BLUE	25
FPTAGY	YELLOW	25
FPTAGG	GREEN	25
FPTAGO	ORANGE	25

Storage Bags



FP1002



FP1004



FP1005



FP1006



FP1007

Storage Bags for Various Equipment

PART NO	DESCRIPTION
FP1002	SMALL MESH EQUIPMENT BAG FOR A HARNESS AND LANYARD COMBO KIT 14" L x 13.5" H
FP1004	SMALL EQUIPMENT BAG FOR BASIC EQUIPMENT KIT - 11.25" L x 11.375" H
FP1005	SMALL EQUIPMENT BAG FOR SELF-RETRACTING LIFELINE OR WINCH 16" L x 16.5" W x 9" H
FP1006	LARGE EQUIPMENT BAG FOR HARNESS, LANYARD, ANCHORAGE CONNECTORS AND MORE 23.5" L x 11.75" W x 12.5" H

Storage Bags for Tripods


PART NO	DESCRIPTION
FP1007	DURABLE ZIPPERED TRIPOD BAG. TO PROTECT YOUR TRIPOD FROM DAMAGE AND DIRT WHILE REDUCING CARRYING EFFORT FOR FP09907 TRIPOD - 58.5" x 10.625" x 12.5"
FP1008	DURABLE ZIPPERED TRIPOD BAG. TO PROTECT YOUR TRIPOD FROM DAMAGE AND DIRT WHILE REDUCING CARRYING EFFORT FOR FP09910 TRIPOD - 96.5" x 12" x 12.75"

Fall Clearance Calculation

Required Distance Scenario One (RD1)

Anchorage is **below** worker's D-ring:


$$RD1 = (E + LL) + (H + Xh) + C + P + HDA$$



Required Distance Scenario Two (RD2)

Anchorage is **above** worker's D-ring:

$$RD2 = (E + LL) + (H + Xh) + C + P - HDA$$



Explanation of Variables

- E = Elongation distance of the deceleration device when it's deployed
- LL = Lanyard Length
- H = Height or distance from the worker's feet to the harness dorsal D-ring
- Xh = System material stretch and D-ring movement
- C = Clearance or extra safety factor
- P = Position of the body (standing/crouching/laying down)
- HDA = Vertical distance from D-ring to the anchorage system

Commonly Used Values

- E = Energy absorber (4.6 ft) or web SRL (3 ft)
- H = D-ring height (5 ft)
- Xh = System material stretch (1 ft)
- C = Clearance recommendation minimum (2 ft)
- P = Standing (0 ft) or crouching (3 ft) or laying down (5 ft)

Example Calculation

If you connect a 6 ft energy absorbing lanyard to an anchorage system 2 ft below your dorsal D-ring while standing, you need a clearance of:

$$RD1 = (E + LL) + (H + Xh) + C + P + HDA$$

$$RD1 = (4.6 + 6) + (5 + 1) + 2 + 0 + 2$$

$$RD1 = 20.6 \text{ ft}$$

FOR OUR COMPLETE LINE OF SAFETY PRODUCTS GO TO WWW.PIPCANADA.CA



HEAD
PROTECTION



EYE AND FACE
PROTECTION



HEARING
PROTECTION



RESPIRATORY
PROTECTION



FALL
PROTECTION



FIRST AID
PRODUCTS



TRAFFIC AND HIGH
VISIBILITY PRODUCTS



WELDING
FACE SHIELD



IDENTIFICATION
PRODUCTS



HAND
PROTECTION



PIP Canada Ltd.

2477 Michelin St | Laval, Quebec H7L 5B9
450-687-7374 | 877-446-3278
orders@pipcanada.ca | www.pipcanada.ca



MKTGFPCATEN122021